

TEST REPORT

CLIENT Lions Floor

TEST METHOD CONDUCTED

ASTM E303 Test Method for Measuring Surface Frictional Properies using the British Pendulum Tester



| DESCRIPTION OF TEST SAMPLE | |
|----------------------------|-------------------|
| IDENTIFICATION | Comfort Heights |
| COLOR | Country Aura |
| ROLL NUMBER | SKU: LI-CH07 |
| CONSTRUCTION | Laminate Flooring |

PROCEDURE

This test method provides the method of using the British Pendulum Tester to measure the "skid resistance" or frictional properties of a test surface. The dynamic pendulum impact tester is used to measure energy loss when a rubber edge slider is propelled over a test surface. The test material was tested in 4 directions with the average BPN (British Pendulum Number) reported. A lower BPN indicates a more slippery surface.

TEST RESULTS

| CONDITION | BPN |
|------------------------|-----|
| Rubber Heel Tested Dry | 54 |
| Rubber Heel Tested Wet | 29 |



APPROVED BY:

Lang aslung

This report is provided for the exclusive use of the client to whom it is addressed. It may be used in its entirety to gain product acceptance from duly constituted authorities. This report applies only to those samples tested and is not necessarily indicative of apparently identical of similar products. This report, or the name of Professional Testing Laboratory Inc. shall not be used under any circumstance in advertising to the general public.

714 Glernwood Place Dalton, GA 30721 Phone: 706-226-3283 Fax: 706-226-6787 email: protest@optilink.us