

## **TEST REPORT**

DATE: 02-26-2021	Page 1 of 1	<b>TEST NUMBER</b> : 0274334
CLIENT	Lions Floor	
	ASTM E387 Standard Test Me	thad for Measuring Thickness of

TEST METHOD CONDUCTED	ASTM F387 Standard Test Method for Measuring Thickness of
TEST METHOD CONDUCTED	Resilient Floor Covering with Foam Layer

## 

DESCRIPTION OF TEST SAMPLE		
IDENTIFICATION	Lions Floor Grande Collection	
CONSTRUCTION	SPC	
BACKING	EVA	

## **GENERAL PRINCIPLE**

The total thickness of a resilient flooring material is determined through measurements made using a .250 inch presser foot and a dial micrometer. The average of 5 total measurements is reported as the average total thickness.

## **TEST RESULTS**

	THICKNESS
SPECIMEN 1	0.260 Inch
SPECIMEN 2	0.258 Inch
SPECIMEN 3	0.261 Inch
SPECIMEN 4	0.260 Inch
SPECIMEN 5	0.261 Inch

AVERAGE TOTAL THICKNESS	0.260 Inch

APPROVED BY:

Gary asbury



This facility is accredited by the National Voluntary Laboratory Accreditation Program for the specific scope of accreditation under Lab Code 100297. This accreditation does not constitute an endorsement, certification, or approval by NIST or any agency of the United States Government for the producttested. This report is provided for the exclusive use of the client to whom it is addressed. It may be used in its entirety to gain product acceptance from duly constituted authorities. This report applies only to those samples Lestedand is not necessarily indicative of apparently identical or similar products. This report, or the name of Professional Testing Laboratory, Inc. shall not be used under any circumstance in advertising to the general public.



714 Glenwood Place

Dalton, GA 30721

706-226-3283

Fax: 706-226-6787