

TEST REPORT

TEST METHOD CONDUCTED	ASTM	F925	(Regular)	Standard	Test	Method	for	Resistance	to
	Chemicals of Resilient Flooring								



DESCRIPTION OF TEST SAMPLE				
IDENTIFICATION	Lions Floor Versa Collection			
CONSTRUCTION	SPC			
BACKING	EVA			

TEST RESULTS

5 MINUTE RATINGS	24 HOUR RATINGS

CTAINING ACENT	SURFACE	SURFACE	COLOR	SURFACE	SURFACE	COLOR
STAINING AGENT	DULLING	ATTACK	CHANGE	DULLING	ATTACK	CHANGE
5% Acetic Acid	0	0	0	0	0	0
70% Isopropyl Alcohol	0	0	0	0	0	0
Mineral Oil	0	0	0	0	0	0
5% Sodium Hydroxide	0	0	1	0	0	1
5% Hydrochloric Acid	0	0	0	0	0	0
5% Ammonia	0	0	0	0	0	0
Bleach	0	0	0	0	0	0
5% Phenol	0	0	0	0	0	0
Gasoline	0	0	0	0	0	0
Sulfuric Acid	0	0	0	0	0	0
Kerosene	0	0	0	0	0	0
Olive Oil	0	0	0	0	0	0

RATING KEY

- 0 No change (----)
- 1 Slight change
- 2 Moderate change
- 3 Severe change

APPROVED BY:

This report is provided for the exclusive use of the client to whom it is addressed. It may be used in its entirety to gain product acceptance from duly constituted authorities. This report applies only to those samples tested and is not necessarily indicative of apparently identical of similar products. This report, or the name of Professional Testing Laboratory Inc. shall not be used under any circumstance in advertising to the general public.

714 Glernwood Place Dalton, GA 30721 Phone: 706-226-3283 Fax: 706-226-6787 email: protest@optilink.us

Lan atluny