





Lions Floor District collection was created with exclusive patterns topped with intricate wood grain embossed finishes to coordinate with various design options. Featuring a fiberglass-reinforced structure, the product delivers dimensional stability that yields high traffic tolerance. The District collection is an embodiment of timeless aesthetics and performance-driven functionality.





Waterproof

SPECIFICATIONS



Indent Resistant



Sound Tested









Phthalate Free

JILCHICAI	10103						
Material Type	LVP	Edge Profile	Square Edge	Per Box	20 pieces	48.33 sc	ı.ft. 39 lbs.
Plank Size	4' x 7 ¼″	Installation Type	Glue Down	Pallet	60 boxes	2,900 sq	.ft. 2,390 lbs.
Total Thickness	2 mm	Plank Repeat	10	Containe	r 1,140 boxe	s 55,091 s	q.ft.
Wear Layer	6 mil	Texture/Style Wood	l Grain Embossed	KED WA	Real A	DWARRA	CI
Attached Pad	No	Finish UV	/ Aluminum Oxide				score
Luxury Vinyl Plank		Fiberglass-Reinf	orced Structure		TIAL LIGHT		· · · · · · · · · · · · · · · · · · ·

C CERTIFIED BY SCS Global Services

	Fiberg	lass-l	Reinf	orced	Stru	cture	e



District



COLORS



LI-DT01 Billings



LI-DT04 Brentwood



LI-DT07 Carmel



LI-DT10 Irvine



LI-DT02 Chesterbrook



LI-DT05 Brighton



LI-DT08 Clayton



LI-DT11 Arlington



LI-DT03 Los Alamos



LI-DT06 Ardmore



LI-DT09 Bellevue



LI-DT12 Westfield

TESTING					
ASTM E648	Fire Rating	Class 1 or 2	ASTM F410	Average Wear Layer Thickness	6.0 mil
ASTM E303	Surface Friction (in BPN)	Dry 77 Wet 37	ASTM F2199	Dimensional Stability, Curl After Heat	Passes
ASTM F2421	Size and Squareness	Above average	ASTM F1514	Resistance to Heat	Passes
E492	IIC - Impact Sound Rating	39 db	ASTM F1514	Resistance to Light	Passes
E90	STC - Sound Transmission Loss	53 db	ISO 24337	Variance of Thickness	Above avg.
ASTM D1308	Stain Resistance	No Stain		Floor Score Certified	