



LionsGrip is our standard-grade resilient flooring adhesive designed for consistent, efficient installs. It features a transitional pressure-sensitive formula ideal for residential and light commercial environments.

MVER

12 lbs

Key Benefits:

 Transitional Pressure Sensitive Adhesive

PH NTR 5-12

- Ideal for LVP/LVT, sheet vinyl, and rubber
- One-part system for easy application
- Light traffic ready in ~12 hours
- Ultra-low VOC formula (≤ 11 g/L) for healthier indoor air
- Compliant with stringent indoor air quality standards
- LEED-compatible adhesive for eco-conscious projects
- Budget-conscious solution

Application Method:

Flash Time

30-60 min*

Spread & set (PSA method)

Working Time

12 hrs

Coverage: 150–260 ft² per gallon

Approved Flooring Types:

- LVP / LVT (non-porous)
- Sheet Vinyl (heterogeneous / homogeneous)
- Rubber Tile (light commercial)

Best For:

- Standard residential projects
- · Light commercial spaces
- Cost-effective flooring jobs

Tools • Herramientas

Light Traffic

Measurements = Width × Depth × Spacing

BOND ONLY



Cure Time

12 hrs

1/16" × 1/32" × 1/32" U Notch 220-260 ft2/gal

Heavy Traffic

RESILIENT: Modular (LVP/LVT [non-porous], SVT, VCT, VET), Sheet (heterogeneous/homogeneous [non-porous])



1/16" × 1/16" × 1/16" Sq Notch 150-180 ft2/gal

RESILIENT: Linoleum, Modular (LVP/LVP [porous], woven, rigid core [dryback]), Rubber (crumb, sheet, tile, semi-wet), Sheet (heterogeneous/homogeneous [porous]), Stair Treads (rubber/vinyl [porous], semi-wet)



3/8" Short Nap Paint Roller Up to 350 ft2/gal

RESILIENT: Sheet (fiberglass)

SKU: LI-LionsGrip-4gal **Packaging:** 48 buckets per pallet



