









12 lbs





rking Time Cure Tim
12 hrs 12 hrs



Light Traffic

0 min*



LionsGrip is our firm-set resilient flooring adhesive designed for consistent, efficient installs. It features a transitional pressure-sensitive formula ideal for residential and light commercial environments.

Key Benefits:

- Transitional Pressure Sensitive Adhesive
- Ideal for LVP/LVT, sheet vinyl, and rubber
- One-part system for easy application
- Light Traffic: 0 min (PSA), 12 hrs (Semi-wet-set)
- Ultra-low VOC formula (≤ 11 g/L) for healthier indoor air
- Compliant with stringent indoor air quality standards
- LEED-compatible adhesive for eco-conscious projects
- · Budget-conscious solution

Application Method:

- Spread & set (PSA method)
- Coverage: 150-260 ft² per gallon

Approved Flooring Types:

- LVP / LVT (non-porous)
- Sheet Vinyl (heterogeneous / homogeneous)
- Rubber Tile (light commercial)

Best For:

- Standard residential projects
- · Light commercial spaces
- · Cost-effective flooring jobs

Substrate Testing

- RH 99% [ASTM F2170]
- pH 5-12 [ASTM F710]
- MVER 12 lbs [ASTM F1869]

Tools

Measurements = Width × Depth × Spacing

BOND ONLY



1/16" × 1/32" × 1/32" U Notch 220-260 ft2/gal

RESILIENT: Modular (LVP/LVT [non-porous], SVT, VCT, VET), Sheet (heterogeneous/homogeneous [non-porous])



1/16" × 1/16" × 1/16" Sq Notch 150-180 ft2/gal

RESILIENT: Linoleum, Modular (LVP/LVP [porous], woven, rigid core [dryback]), Rubber (crumb, sheet, tile, semi-wet), Sheet (heterogeneous/homogeneous [porous]), Stair Treads (rubber/vinyl [porous], semi-wet)



3/8" Short Nap Paint Roller Up to 350 ft2/gal

RESILIENT: Sheet (fiberglass)

SKU: LI-LionsGrip-4gal **Packaging:** 48 buckets per pallet





*Data reference PSA usage only 888-575-9220 | LionsFloor.com